

# DIGITUS Wall housing 254 mm (10") - 312x300 mm (WxD)

DN-10-06U-B  
EAN 4016032466253



**254 mm (10") 6U wall mounting cabinet 330x312x300 mm, color black (RAL 9005)**

The 254 mm (10") wall mounted cases are made of a robust steel construction. The cable entry openings in the roof and floor offer best possibilities for a proper cable management. The compact housing is therefore ideal for all common EDP and telecommunications applications, especially where space is limited and in private households.

**The DIGITUS® wall-mounted enclosures are manufactured, designed and developed for the high demands of the IT infrastructure.**

- Protection class IP20
- Lockable safety glass door
- 200° door opening angle
- 1-point locking on the front door
- 254 mm (10") profile rails mounted at the front inside the cabinet, galvanized

- 254 mm (10") profile rails are adjustable in depth
- 1.1 - 1.5 strong sheet steel with a high load capacity, powder-coated
- Cable entry with brush strip in the roof and with plastic cover in the floor
- Ventilation slots for active and passive ventilation
- Installation depth for components max.: 240 mm
- IP protection class: IP20
- Color: black, RAL 9005
- Depth: 300 mm
- Front door: Glass door, single opening
- Units: 6
- Load capacity: 30 kg
- Mounted: yes
- Cabinet type: Wall mounting cabinet
- Width: 312 mm

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	6.06	35.50	36.00	40.00	51,120.00
Packaging Unit Inside	1	6.06	35.50	36.00	40.00	51,120.00
Packaging Unit Single	1	6.06	35.50	36.00	40.00	51,120.00
Net single without Packaging	1	5.33	35.50	36.00	40.00	51,120.00

More images:

