

# DIGITUS 1.25 Gbps copper SFP-module, RJ45

DN-81005-01  
EAN 4016032454915



### 1.25 Gbps Copper SFP Module, RJ45, HP-compatible 10/100/1000Base-T, up to 100m, HP

The DIGITUS® Mini GBIC (SFP) transceiver modules offer the highest quality and reliability. The module offers a perfect opportunity for you to extend your Gigabit network switch with a free SFP Uplink Port around an additional RJ45 connection. Thanks to the hot-plug capability, you can install the module without any interruption to the network traffic or restart of the device. In addition, conformity with the MSA (Multi Source Agreement) standard provides compatibility with the current network switch manufacturers.

#### The plug and play extension for your network switch

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Compatible with the following manufacturers: HP
- Up to 1.25 Gbps bidirectional maximum data rate
- Compliant to IEEE 802.3z Gigabit Standard
- High quality and excellent reliability

- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant
- Hot pluggable - installation possible while in operation
- Auto MDI/MDI-X
- Connection: 1x RJ45, CAT 5
- Distance: up to 100 m
- Operating temperature: 0 °C ~ 70 °C
- Manufacturer compatibility: HP, Universal (MSA)
- Connector: RJ45
- DDM Support: no
- Distance (km): 0.1
- Mode: Copper
- Ethernet speed: Gigabit

#### Package contents

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	120	7.00	25.40	39.40	55.00	55,041.80
Packaging Unit Inside	30	1.75	7.00	20.00	30.00	4,200.00
Packaging Unit Single	1	0.06	3.20	9.30	12.00	357.12
Net single without Packaging	1	0.04	3.20	9.30	12.00	357.12

#### More images:





Part Number	Data Center	Speed	Distance	Connector	Weight	Operating Temperature	Industrial Model
<b>SFP Modules</b>							
<b>Fast Ethernet</b>							
DM-0100	4790000000	100 Mbps	20km	LC Duplex OM3	100mg	0 to +70 °C	✓
DM-0102	4790000000	100 Mbps	20km	LC Duplex OM3	100mg	0 to +70 °C	✓
DM-0103	4790000000	100 Mbps	20km	LC Duplex OM3	100mg	0 to +70 °C	✓
<b>10GbE</b>							
DM-0104	4790000000	10 Gbps	20km	LC Duplex OM3	100mg	0 to +70 °C	✓
DM-0105	4790000000	10 Gbps	20km	LC Duplex OM3	100mg	0 to +70 °C	✓
DM-0106	4790000000	10 Gbps	20km	LC Duplex OM3	100mg	0 to +70 °C	✓
DM-0107	4790000000	10 Gbps	20km	LC Duplex OM3	100mg	0 to +70 °C	✓
<b>10GbE SR</b>							
DM-0108	4790000000	10 Gbps	20km	LC Duplex OM3	100mg	0 to +70 °C	✓
DM-0109	4790000000	10 Gbps	20km	LC Duplex OM3	100mg	0 to +70 °C	✓
DM-0110	4790000000	10 Gbps	20km	LC Duplex OM3	100mg	0 to +70 °C	✓
DM-0111	4790000000	10 Gbps	20km	LC Duplex OM3	100mg	0 to +70 °C	✓
DM-0112	4790000000	10 Gbps	20km	LC Duplex OM3	100mg	0 to +70 °C	✓
DM-0113	4790000000	10 Gbps	20km	LC Duplex OM3	100mg	0 to +70 °C	✓
DM-0114	4790000000	10 Gbps	20km	LC Duplex OM3	100mg	0 to +70 °C	✓
DM-0115	4790000000	10 Gbps	20km	LC Duplex OM3	100mg	0 to +70 °C	✓
DM-0116	4790000000	10 Gbps	20km	LC Duplex OM3	100mg	0 to +70 °C	✓
DM-0117	4790000000	10 Gbps	20km	LC Duplex OM3	100mg	0 to +70 °C	✓