

DIGITUS HP-compatible SFP+ 10G SM 1310nm 10Km with DDM

DN-81201-01
 EAN 4016032370031



10G SFP+ Module, Singlemode, DDM, HP-compatible LC Duplex Connector, 1310nm, up to 10km, HP

The DIGITUS® mini GBIC (SFP) transceiver modules offer highest quality and reliability. Whether from switch to switch, converter to switch, converter to converter or any else application: The wide product range of DIGITUS® modules makes possible a flexible usage of the fiber technology. The conformity to the MSA (Multi Source Agreement) standard ensures a compatibility to third party manufacturers.

The plug and play fiber connection

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Supports DDM (Digital Diagnostic Monitoring)
- High quality and excellent reliability
- 10 Gbps Maximum Data Rate
- Compliant to IEEE802.3ae 10 Gigabit Standard
- Class 1 laser product compliant with EN 60825-1
- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant
- Hot pluggable

- Connector: 1x LC Duplex
- Wavelength: 1310nm
- Transmission Power: Minimum -8 dBm, Maximum -0,5 dBm
- Sensitivity Receiving Power: Minimum -12.5 dBm
- For a distance of up to 10,0km
- Safe fast-locking mechanism
- Operating temperature: 0 °C ~ 70 °C
- HP compatible
- HP-Aruba compatible
- Broadcasting Mode: Unidirectional
- Manufacturer compatibility: HP
- Connector: LC
- DDM Support: yes
- Distance (km): 10
- Mode: Singlemode
- Ethernet speed: 10 Gigabit
- Wavelength: 1310 nm

Package contents

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	20	2.00	41.00	26.00	16.00	17,056.00
Packaging Unit Inside	1	0.10	3.00	11.50	9.00	310.50
Packaging Unit Single	1	0.10	3.00	11.50	9.00	310.50
Net single without Packaging	1	0.08	3.00	11.50	9.00	310.50

More images:



SFP Modules							
Part Number	SKU Code	Speed	Distance	Connector	Mounting	Operating Temperature	Industrial Version
Fast Ethernet							
DS-4100	4100000000	100 Mbps	10km	LC-Multifiber Duplex	100mm	0 to 70 °C	✓
DS-4100	4100000010	100 Mbps	20km	LC-Duplex Single	100mm	0 to 70 °C	✓
DS-4100	4100000020	100 Mbps	20km	LC-Duplex BiDi	100mm	0 to 70 °C	✓
10GbE							
DS-4100	4100000000	10 Gbps	10km	LC-Multifiber Duplex	100mm	0 to 70 °C	✓
DS-4100	4100000010	10 Gbps	20km	LC-Duplex Single	100mm	0 to 70 °C	✓
DS-4100	4100000020	10 Gbps	20km	LC-Duplex BiDi	100mm	0 to 70 °C	✓
DS-4100	4100000030	10 Gbps	20km	LC-Duplex Single	100mm	0 to 70 °C	✓
DS-4100	4100000040	10 Gbps	20km	LC-Duplex BiDi	100mm	0 to 70 °C	✓
10G							
DS-4100	4100000000	10 Gbps	10km	LC-Multifiber Duplex	100mm	0 to 70 °C	✓
DS-4100	4100000010	10 Gbps	10km	LC-Duplex Single	100mm	0 to 70 °C	✓
Fast Ethernet							
DS-4100	4100000000	100 Mbps	10km	LC-Duplex Single	100mm	0 to 70 °C	✓
DS-4100	4100000010	100 Mbps	20km	LC-Duplex Single	100mm	0 to 70 °C	✓
DS-4100	4100000020	100 Mbps	20km	LC-Multifiber Duplex	100mm	0 to 70 °C	✓
DS-4100	4100000030	100 Mbps	20km	LC-Duplex Single	100mm	0 to 70 °C	✓
DS-4100	4100000040	100 Mbps	20km	LC-Duplex BiDi	100mm	0 to 70 °C	✓
DS-4100	4100000050	100 Mbps	20km	LC-Duplex Single	100mm	0 to 70 °C	✓
DS-4100	4100000060	100 Mbps	20km	LC-Duplex BiDi	100mm	0 to 70 °C	✓